

Технические характеристики муфт МУВП

Номер муфты	Номинальный крутящий момент Ткр, Нхм	d	d1	d	d1	D, не более	L, не более, для исполнений				l, h14, не болсе, для исполнений				Частота вращения, с-1, не более	Масса, кг						
		H8	H9	H8	H9		1	2	3	4	1	2	3	4								
		Ряд 1	Ряд 2																			
МУВП-1	6,3	9	-	71	43	-	43	-	20	-	13	-	147	0,58								
		10	-		49	43	49	-	23	20	16	-		0,60								
		11	-											0,59								
МУВП-2	16,0	12	-	75	63	53	63	-	30	25	20	-	127	0,70								
		14	-		83	59	83	59						0,68								
		16	-											0,75								
МУВП-3	31,5	16	-	90	84	60	84	60	40	28	30	18	106	1,52								
		18	-											1,40								
		-	19											1,38								
МУВП-4	63,0	20	-	100	104	76	104	76	50	36	38	24	95	2,02								
		22	-											2,04								
		-	24											1,96								
МУВП-5	125,0	25	-	120	125	89	125	89	60	42	44	26	77	3,97								
		28	-											4,13								
		-	30											4,37								
МУВП-6	250,0	32	-	140	165	121	165	121	80	58	60	38	63	5,91								
		-	35																			6,21
		36	-																			6,25
		-	38																			6,28
		40	-																			6,63
		-	42																			6,86
МУВП-7	500,0	45	-	170	225	169	225	169	110	82	85	56	63	6,80								
		40	-																			11,75
		-	42																			12,10
МУВП-8	710,0	45	-	190	226	170	226	170	110	82	85	56	50	14,31								
		-	48																			14,70
		50	-																			15,21
		-	55																			15,34
		56	-																			15,22
МУВП-9	1000,0	50	-	220	286	216	286	216	140	105	107	72	48	18,87								
		-	55																			19,91
		56	-																			19,75
		-	60																			21,93
		63	-																			26,09
		-	65																			28,65
МУВП-10	2000,0	63	-	250	288	218	288	218	140	105	107	72	38	31,98								
		-	65																			31,64
		-	70																			34,65
		71	-																			34,48
		-	75																			35,06
		80	-																			36,07
МУВП-11	4000,0	80	-	320	348	268	348	268	170	130	135	95	30	38,45								
		-	85																			40,03
		90	-																			66,71
		-	95																			69,01
МУВП-12	8000,0	100	-	400	432	342	432	342	210	165	170	125	24	74,11								
		-	110																			132,68
		-	120																			140,88
		125	-																			145,58
МУВП-13	16000,0	-	120	500	435	345	435	345	250	200	205	155	19	142,98								
		125	-																			237,81
		-	130																			234,61
		140	-																			264,31
		-	150																			264,61
		180	-		615	495	615	495	300	240	245	185		356,31								
														308,11								

Пример обозначения : Муфта упругая втулочно-пальцевая МУВП - 7 - 500 - 40 - 1 - 45 - 4 УЗ:
муфта втулочно-пальцевая с номинальным крутящим моментом 500 Н х м, одна втулка с диаметром посадочного отверстия 40 мм, исполнения 1, другая - диаметром 45 мм, исполнения 4, климатическим исполнением У и категорией размещения 3.